16156 BEDFORD, NH LOCATION MAP 0.25 0.125 0 0.25 0.5 ml.

GRAPHIC SCALE: 1"-174 MILE

THE STATE OF NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION


CONSTRUCTION PLANS

FEDERAL PROJECT X-A001 (160)

NH PROJECT NO. 16156

NH ROUTE 114


BOWMAN BROOK CULVERT REHABILITATION



DESIGN DATA

AVERAGE DAILY TRAFFIC 2016 AVERAGE DAILY TRAFFIC 2016 PERCENT OF TRUCKS DESIGN SPEED LENGTH OF 16156 PROJECT

5% 45 MPH D.11 MICE



TOWN OF BEDFORD

COUNTY OF HILLSBOROUGH

SCALE: 1" = 50"

RECOMMEN

THE STATE OF NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION

STREET OF PROJECT DESCRIPTION

8/15/2017

8/16/17

APPROVED: DISTRIBUTED AND COLEY ENGINEER

FEBRUAL PROJECT NO. STATE PROJECT NO. SMEET NO. TUTAL SMEETS

X-A001(16D) 16156 1 23

2 6

TJV.

DEAT OF STREET



GENERAL NOTES

	INDEX OF SHEETS
ET NO.	DESCRIPTION
1	TITLE PAGE
2	INDEX OF SHEETS AND GENERAL NOTES
3,4	STANDARD SYMBOLS
5	ACCESS TYPICAL SECTION
6	SUMMARY OF QUANTITIES
	BRIDGE PLANS
7-23	NH ROUTE 114 OVER BOWMAN BROOK (BRIDGE NO, 151/151)

- 1) FOR STANDARD PLANS, SEE "STANDARD PLANS FOR ROAD CONSTRUCTION" DATED 2010 (A BOUND BOOK).
- THIGH TENSION OVERHEAD TRANSMISSION LINES ARE LOCATED THROUGHOUT THE PROJECT WITH CROSSINGS AT VARIOUS LOCATIONS AND RUNNING ALONG THE ROAD THROUGHOUT THE PROJECT EVEN ON REGULAR POLES. THE CONTRACTOR IS ADVISED THAT EXTREME CAUTION WILL BE REQUIRED IN THE OPERATION OF EQUIPMENT. ESPECIALLY CRANES AND PILE DRIVING EQUIPMENT.
- MODIFY SUPERELEVATION ON EXISTING CURVES BY THE USE OF A LEVELING COURSE TO THE RATES INDICATED ON THE PLANS OR AS ORDERED.
- EXISTING DELINEATORS AND WITNESS MARKERS THAT ARE REMOVED AND DETERMINED BY THE ENGINEER TO BE IN ACCEPTABLE CONDITION SHALL BE RESET (SUBSIDIARY). ADDITIONAL DELINEATORS AND WITNESS MARKERS ORDERED WILL BE PAID UNDER THE APPROPRIATE ITEMS OF THE CONTRACT.
- NO EXISTING MONUMENTS, BOUNDS, OR BENCHMARKS SHALL BE DISTURBED WITHOUT FIRST MAKING PROVISIONS FOR RELOCATION.

- 6 PERFORM ALL WORK WITHIN THE EXISTING RIGHT-OF-WAY. UNLESS OTHERWISE SHOWN ON THE PLANS OR AS ORDERED BY THE ENGINEER.
- (7) REMOVE UNPROTECTED PROJECT MARKERS (SUBSIDIARY).
- B SURVEY DATA FOR THIS PROJECT WAS COLLECTED BY SDR AND THE FIELD NOTES CAN BE FOUND IN THE SURVEY FIELD BOOK(S) 13399 & 10096, COORDINATES ARE NEW HAMPSHIRE STATE PLANE COORDINATES OF NAD83, 1986 ADJUSTMENT AND THE BEARINGS ARE GRID, ELEVATIONS ARE REFERENCED TO NGVD 1929.
- QUANTITIES FOR EMBANKMENT AND EXCAVATION FOR SLOPE ROUNDINGS AS SHOWN ON THE TYPICALS HAVE NOT BEEN CALCULATED AND ARE NOT INCLUDED IN THE QUANTITY SUMMARIES. AND ARE CONSIDERED SUBSIDIARY TO THE APPROPRIATE 203 ITEMS.


	THE FOLLOWING GENERAL NOTES WILL BE USED ON THIS PROJECT:											
①	(2)	0	(1)	(3)	(6)	7	(8)	0	0	0	0	
0	0	0	0	0	0	0	0	0	0	0	0	


STATE OF NEW HAMPSHIRE


DEPORTMENT OF TRANSPORTATION . BUREAU OF HIGHWAY DESIGN

INDEX OF SHEETS AND GENERAL NOTES

newibide bare	DDY	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
9-1-2016	DZ_Index_sheet	16156	2	23







STATE OF NEW HAMPSHIRE

DEPORTNENT OF TRANSPORTATION . BUREAU OF HIGHWAY DESIGN

ACCESS TYPICAL SECTION

Stantec

SUMMARY OF QUANTITIES (ESTIMATED) THIS INFORMATION IS FOR BIDDING PURPOSES ONLY

						D	RAINAG	E SUMI	MARY			
	202.41	202.42	207.3	B£3. B	585.3401	593.411	602.41190	503 9021E	303.33212	803.99012	622 f	
REF. NO		RÉMOVAL OF EXISTING PIPE OVER 24" CIAMETER	UNCLASSIFIED CHARNEL EXCAVATION	RPRAP CLASS V	SIMULATED STREAMBED MATERIAL	GEOTEXTILE: PERM, CONTROL OL 1, NON-WOVEN	CENTREUGALLT CAST CONCRETE LINER FOR BU' (AIP	15° R.C. PIPE. 20000	2" CORR POLYETHYLENE END SECTION	IZ' TEMPORARY DRAIN PIPE	STEEL WITNESS MARKERS	RE.MARKS
	LF	LF	CY	CY	CV	SY	LF	LF	EA	LF	EA	
NH ROUTE 114												
81							210	16.				
02	1	14	165	45	15	142		16			1.	
83		14	167	23	18	1B2					1.	
£1	19											REMOVE 19' x 15" RDP
E2												
E3	21											REMOVE 21' x 15" RDP
T									1.	68		
2												REMOVE 88' x 12" TEMP, DRAIN FIRE & END SECTION (SUBSIDIARY TO NOTE T1)
SUB-FOTAL	40	28	362	200	31	324	210	32	1	68	-2	
ROUNDING	0	2	£	2	4.	-28	0	п	0	2	0	
TOTAL	40	30	370	210	35	350	210	32	1	70	2	-

	500.0201 - ACCESS FOR BRIDGE CONST	RUCTION								
SUBSIDIARY ITEMS										
ITEM NO.	ITEM	QUANTITY	UNIT							
203.1	COMMON EXCAVATION	144	CY							
203,801	EMBANKWENT-N-PLACE	85	CY							
304.301	CRUSHED GRAVEL	36	CY							

NOTE: THIS LIST SHOULD NOT BE CONSIDERED TO SE A LIST OF ALL SUBSIDIARY WORK PRESENT IN THE PROJECT. REFER ALSO TO THE PROPOSAL, SPECIAL PROVISIONS AND THE STANDARD SPECIFICATIONS.

SUBSIDIARY ITEMS											
ITEM NO.	ITEM	QUANTITY	UMIT								
203.1	COMMON EXCAVATION	90	CY								
203,601 304,301	EMBANKMENT-IN-PLACE CRUSHED GRAVEL	52 23	CY								

			¢	PACLU	NOEO N	LITEM NO	619.1)			
SIGN	DESCRIPTION	SIZ	E (ff)	SF	NO.	TOTAL AREA	PORTABLE	U- CHANNEL	REMARKS	
NO		W	Н	\Box	HELL	(8F)	mi min	POSTS		
326-2A	"END ROAD WORK"	4	2	8	4	32	4		BLACK/ORANGE.	
R50-1	"NH LAW WORK ZONE"	6	4	24	2	48	2		BLACKWHITE	
A/20-1 _m	"ROAD WORK AHEAD"	4	4	16	2	32	2		BLACKIFLUORESCENT ORANGE	
W20-1b	"ROAD WORK 500 FT"	4	4	16	2	32	2		BLACK/FLUORESCENT ORANGE	
W20-1c	"ROAD WORK 1000 FT"	4	4	16	2	32	Z		BLACK/FLUORESCENT ORANGE	
VZ0-1e	"ROAD WORK 1/2 MILE"	4	9	16	2	32	2		BLACK/FLUORESCENT CRANGE	

NOTE: The estimated quantities of "Premaners Controls" are hearby listed. The contractor is responsible for all "Operational Controls" inquire under section 619 of the NHDOT Specifications and the Manual of Uniform Traffic Control Devices (MHDOD) Part

ITEM NO.	ITEM	QUANTITY	UNIT
201.1	CLEARING AND GRUBBING (F)	0.1	A
ZU1.8813	INVASIVE SPECIES CONTROL TYPE 1	JbU	57
202.7	REMOVAL OF GUARDRAL	390	LF
203 11	COMMON EXCAVATION - LRS	410	CX
203 55543	GUARDRAIL EAGRT OFFSET PLATFORM, TL3	1	LI
283 601	EMBANKMENT IN PLACE	2/2	CY
206.19	COMMON STRUCTURE EXCAVATION EXPLORATORY	70	CY
304 32	CHUSHED GRAVEL FOR SHOULDER LEVELING	25	TON
866 012	WIGG STEEL POST REPLACEMENTS FOR BEAM GUARDRAL POSTS	15	EA
606 D122	W6X9 STEEL POST ASSEMBLIES FOR BEAM GUARDRAIL POSTS	15	EA
636 1234	BEAM QUARDRAS, (TERMINAL UNIT TYPE EAGRT, IL 3) (STEEL POST)	3	U
606,18001	31" W-BEAM GUARDRAIL WITH 8" OFFSET BLOCK ISTEEL POST)	350	LF
606.34202	SINGLE FACED ASYMMETRICAL TRANSITION RAIL RIGHT (STEEL POST)	2	u
606 417	PORTABLE CONCRETE BARRIER FOR TRAFFIC CONTROL	400	LF
606.91	RESETTING OR SETTING GUARDFAIL	25	LF
606 P513	TEMP, IMPACT ATTENUATION DEVICE (REDIRECTIVE) TEST LEVEL 3	4	U
515,034	RELOCATING TRAFFIC SIGN, TYPE C	- 1	U
618.61	UNIFORMED OFFICERS WITH VEHICLE	4	S
618.7	FLAGGERS	250	HB
619.1	MAINTENANCE OF TRAFFIC	3	t
619.25	PORTABLE CHANGEABLE MESSAGE SIGN	2	U
621.2	RETROREFLECTIVE BEAM GUARDRAD DELINEATOR	6	EÁ
621,31	SINGLE DELINEATOR WITH POST	4	EΑ
621.32	DOUBLE DELINEATOR WITH POST	1	EA
832 0104	RETROREFLECTIVE PAINT PAVE, MARKING, 4" LINE	2300	LF
643.22	FERTILIZER FOR REFERTILIZATION	0.3	TON
645.3	EROSION STONE	350	TON
645.44	TEMPORARY SLOPE STABILIZATION, TYPE D (WILDLIFE FRIENDLY)	2450	SY
645.512	COMPOST SOCK FOR PERIMETER BERM	1100	LF
845.52	RYEGRASS FOR TEMPORARY EROSION CONTROL.	50	LB
645,531	SLT FENCE	1100	LF
645 7	STORWINATER POLILITION PREVENTION PLAN (SWPPP)	1	U
645 T1	MONITORING SWPPP AND EROSON AND SEDIMENT CONTROLS	90	HA
646.4	TURF ESTABLISHMENT WITH MULCH, TACKIFIERS AND HUMUS	0.6	A
670,104	TEMPORARY PORTABLE LIGHTING	2	Ü
692	MOBILIZATION	3.	U
697 11	INVASIVE SPECIES CONTROL AND MANAGEMENT PLAN	.1	Ų
697.34	PROJECT OPERATIONS PLAN	7	11
699	MISCELLANEOUS TEMPORARY EROSION AND SEDIMENT CONTROL	4	- 5
1010.15	FUEL ACJUSTMENT	4	- 5

" NOT A BID ITEM


Stantec _

STATE OF NEW HAMPSHIRE

DEPORTNENT OF TRANSPORTATION . BUREAU OF HIGHWAY DESIGN

SUMMARY OF QUANTITIES

e Con	STATE PROJECT NO.	SHEET NO.	TOTAL SHEETS
05_055	16156	6	23



DESIGN LOADS, MATERIALS AND SPECIFICATIONS

- I. DESIGN LOADINGS HL-93
- # DESIGN NETHOD: LOAD AND RESISTANCE FACTOR DESIGN (LAPPO)
- 3. SPECIFICATIONS4 AASHTO 2014 LRFC BP) DGE DESIGN SPECIFICATIONS AS AMENDED AASHID BRIDGE CONSTRUCTION SPECIFICATIONS WITH INTERIMS MHDOR 2016 STANDARD SPECIFICATIONS FOR ROAD & BRIDGE
- 4. FOLKDATION DATA: REINFORCED CONCRETE FOOTINGS SUPPORTED ON BEGROOK WITH THE FOUR OF STRUCTURAL FILL, NOW) WAL BEARING RESISTANCE DE 12 1SE MITH & 0.45 RESISTANCE FACTOR. MUMINAL SLIDING RESISTANCE I TAN 11 DF 34 DEGREES WITH A 0-8 RESISTANCE FACTOR
- B. REINFORGING STEELY MASHID WIT LASTE 4615) GRADE GO.

(TEM 520-213) CONGRETE BLASS B. FODTINGS (ON SOIL) (F)

5000 psi

HEALDWOLLS SHE WINGWALLS: ITEM 520-12, CONCRETE CLASS AT ABOVE FOOTINGS (F)

3000 pm (

GENERAL NOTES

- 1. EXISTING BRIDGE PLANS ARE AVAILABLE UN-LINE IN THE BID PACKAGE ON THE INVITATION TO BIG WES PAGE GURDING THE SIDDING PERIOD. AFTER THE CONTRACT HAS SEEN AMARDED. A SET OF EXESTENCE PLANS WILL BE FORMARDED TO THE CONTRACTOR UPON RECLEST.
- 2. THE CONTRACTOR SHALL FIELD VERDER ALL DIMENSIONS AND ELEVATIONS OF THE EXISTING STRUCTURES AND SHALL BE PREPARED TO MAKE ANY ADMISTMENTS PEGULIARD TO PROPERLY COMPLETE THE CONSTRUCTION OF PROPOSED STRUCTURES,
- 3. THE CONTRACTOR SHALL TAKE ALL NECESSARY MEASURES TO EMSERE THAT DEBRIS DOES NOT FALL INTO THE WATERWAY. THE WATER LEVEL OF THE BOWNAM BROOM WAY VARY FROM WHAT WHICH IS SHOWN. ALL COSTS FOR PROTECTIVE STRUCTURES OR SHIELDING REQUIRED OR DRDERED SHALL BE FAIR DEDER THEM 202.42 AND SHALL INCLUDE ERECTION, WAINTEWANCE, AND REMOVAL OF TEMPORARY STRUCTURES OF OTHER SUCH METHODS AS APPROVED BY THE ENGINEER,
- 4. NO SCAFFOLDS SHALL BE ERECTED OF OPERATIONS COMBUCTED IN THE MATERNAY, UNLESS APPROVED BY THE ENGINEER.
- 5. NO EXISTING MONUMENTS: BOUNDS: DR BENCHMARKS SHALL BE DISTURBED MITHOUT FIRST MAKING PROVISIONS FOR RELOCATION.
- 6. ALL EXPOSED EDGES OF CONCRETE SHALL BE CHAMPERED 34. UNLESS NOTED OTHERWISE.
- 7. SHEAR REYS SHALL BE 3" HIGH BY DME-THIRD THE THICKNESS OF THE WALL- CENTERED. UMLESS NOTED DIHERWISE.
- 6- FOR BORING NOTES SEE BRIDGE SHEET 6-
- 9. FOR HYDRAULIC DATA SEE BRIDGE SHEET 1.

CONSTRUCTION ACCESS NOTES

- 1. | TEW 500-0201 AND 500-0202. ACCESS FOR BRIDGE CONSTRUCTION: SHALL INCLUDE THE DESIGN. CONSTRUCTION, MAINTENANCE, AND REMOVAL OF ALL TEMPORARY ACCESS MEASURES SELECTED BY THE CONTRACTOR FOR THE BRIDGE CONSTRUCTION. INCLUDING ACCESS ACROSS FORMAN BROOK BETWEEN THE HEADWALLS AND WINSWALLS AND ACCESS FROM THE ROADWAY DOWN TO THE PROOF LEVEL AT BOTH HEADWALLS. SEE THE SPECIAL FROM SION FOR ITEMS SOCIORON AND SOCIOROR FOR ADDITIONAL INFORMATION.
- TEMPORARY FILLS CONSTRUCTED ACROSS WEILAND AREAS DODER THIS ITEM SHALL BE LOCATED WITHIN THE ALLOWABLE WERLAND IMPACT AREAS SHOWN ON THE WERLAND PERMIT AND WITHIN THE EASEMENTS SHOWN ON THE SITE PLAN. CLEAN STONE WITH UNDEPLYING GEOTERTILE SHALL BE USED FOR THE TEMPORARY FILLS WITHIN THE WETLAND IMPACT AREAS. ALL COSTS SHALL BE SDB510(APY TO LIEW 500,0201 AND 500,0202.

REINFORCEMENT NOTES

- REINFORCEMENT IN THE BOTTOM OF FOOTINGS SHALL HAVE I'MINIMUM CLEAR COVER-ALL OTHER REINFORCEMENT SHALL HAVE A Phy MINIMUM CLEAR COVER, UNLESS DIMERWISE
- 2. PLACE REINFORCING STEEL ID ANDIO WEEPERS.
- 3. REINFORCING LEGENDS SP SPACE, SPL SPLICE, ES FAF SIDE, NS MEAR SIDE, BOT = BOTTOM. ALT = SCIERNATING. CON = DONEL.
- C. REINFORCING SHALL BE PAID UNDER ITEM 544. REINFORCING STEEL IFF.

HEADWALL AND WINGWALL NOTES

- MEEPERS SHALL BE PLACED SYMMETRICALLY 10"-0" APART AND CENTERED AT 12" ABOVE THE TUP OF FUUTING. WEEPERS SHALL BE 4" DIAMETER AND SLOPED TO DRAIN AT 17:11. ALL COSTS WILL BE SUBSIDIARY TO LIEW 920-12.
- 2. (TEM 536-2. BARP)ER MEMBRONE, PEEL AND SIJGA VERTICAL SURFACES (F). 2 WIDE. SHALL BE PLACED CENTERED OVER ALL VERTICAL CONSTRUCTION JOINTS WITH PROTECTION
- I. ITEM 534.3. WATER REPELLENT I SOLANE-SILOXANEI. SHALL BE APPLIED TO ALL EXPOSED CONCRETE SURFACES OF HEADWALLA AND WINGWALLS TO 1"-0" BELOW FILL LINES.

EXISTING CULVERT REMOVAL NOTES

- 1. JIEW 202,42., REMOVAL OF EXISTING PIPE, OVER 24" DIAMETER, UNLESS DIMERWISE SHOWN ON THE PLANS. SHALL INSTUDE THE FOLLOWING:
 - COMPLETE REMOVAL OF THE MITEPED END PORTIONS OF THE EXISTING COLVERT TO THE LIMITS SHOWN BY THE PLANS, OR AS DIRECTED BY THE ENGINEER
- # DURING REMOVAL OPERATIONS. EXTREME CARE SHALL BE TAKEN NOT TO DAMAGE THE EXISTING COLVERT THAT IS TO PEMEN IN PLACE - ANY DAMAGE SHALL BE INNECTATELY REPORTED TO THE ENCINEER AND REPAIRED AS DIRECTED. AT THE CONTRACTOR'S EXPENSE.
- 1. ECCAVATION. TEMPORARY EARTH SUPPORT AND GRADING. AND BACKFILL NOT INCLUDED IN OTHER THEMS. BUT PEDUTAED FOR REMOVAL OF THE EXISTING STRUCTURE SHALL BE SUESIDJARY TO JTEM 202.42.

COFFERDAM NOTES

- ALL COFFERDAM JIEMS COVERED UNDER SECTION SON OF THE SPECIFICATIONS SHALL BE DESIGNED BY A PROFESSIONAL ENGINEER LICENSED IN THE STATE OF WH. THE CONTRACTOR SHALL SUBMIT STANPED WORKING GRANINGS AND CALCULATIONS FOR DUCUMENTATION IN ACCORDANCE WITH 105.02.
- 2. THE COFFERDAM STEWS ARE INCLUDED IN THE CONTRACT FOR THE PURPOSE OF SUPPORTING EXCAVATIONS FOR THE INLET AND DUTLET HEADWALLS AND WINGWALLS BELOW OVERLYING
 FACILITIES (4-0. EXISTING SEWER AND ROADWAY). EXCAVATION BACKSLOPES IN SOIL BELOW THE OVERLYING FACILITIES SHALL BE HO STEEPER THAN TISHTIYE FLATTER BACKSLOPES SHALL BE USED IF THE CONTRACTOR'S STABILITY CALCULATIONS INDICATE INSUFFICIENT SOIL SLOPE STABILITY AT 1.5H: IV.
- J. THE LOCATION AND LIMITS OF THE COFFERDAMS DETAILED ON THE FLANS ARE SCHEWATIC AND NOT INTEMDED FOR FINAL BESIGN OF THE COFFERDAM, THE COFFERDAM LIMITS AND LOCATION WAY BE ADJUSTED BY THE CONTRACTOR TO ACCOMPUDATE THE CONTRACTOR'S MEANS AND METHODS OF CONSTRUCTION. THE COFFERDAM SHALL BE DESIGNED TO MEET THE REQUIREMENTS OF SECTIONS BOX AND BOX. THE FOLMBATION NOTES AND ALL ENVIRONMENTAL PERMITS.
- OLI COSTS ASSOCIATED WITH THE DESIGN, INSTALLATION, MAINTENANCE, AND REWOVAL DE THE COFFERDAM WILL BE PAID FOR UNDER COFFERDAM TYEMS 503,201 AND 503,207. ALL DEWATERING COSTS FOR THE JOLET AND DITTLET HEADWALL AND WINCHALL EXCAVATIONS WILL BE PAID UNDER STEM 503.707.
- 5. COFFERDANG THAT ARE OUT OFF AND LEFT IN PLACE AT THE CONTRACTOR'S CHOOSE SHALL BE CIT OFF A MINIMUM OF 3 FEET BELOW FIHAL BRADE, HO ADDITIONAL PAYMENT WILL BE MADE FOR COFFERDAMS THAT ARE CUTOFF AND LEFT IN PLACE.
- 6. ALL COSTS ASSOCIATED WITH THE RE-PESISN AND RE-INSTALLATION OF COFFERDAMS DUE TO SUBSURFACE CONDITIONS ENCOUNTERED DURING THE COFFERDAM INSTALLATION THAT ARE DIFFERENT FROM WHAT THE COFFERDAM DESIGNER ASSUMED AND/OR PATERPRETED FROM THE AVAILABLE SUBSUBFACE INCORMATION SHALL BE SUBSIDLERY TO THE ASSOCIATED COFFERDAM ITEM, SECTION 102,05 SHALL BE REFERENCED FOR ADDITIONAL INFORMATION RECARDING THE USE OF SUBSURFACE INFORMATION PROVIDED IN THE CONTRACT.

WATER DIVERSION STRUCTURE NOTES

- 1. THE WATER DIVERSION STRUCTURE ITEM IS INCLUDED IN THE CONTRACT FOR THE PURPOSE OF DIVERTING BOWMAN BROOK AND ANY SURFACE WATER FROM:
 - JAIES AND OUTLES HEADWALL EXCENATIONS
 - WINDWALL EXCAMATIONS
 - PIPE LINER INSTALLATION AND DEMATERING FROM:

 - INTER AND OUTLER HEADWALL EXCENSTIONS
 - WINGWALL EXCAVATIONS
- PIPE LINER INSTALLATION THIS STAGLE ITEM SHALL BE USED FOR BOTH THE INLET AND OUTLET LOCATIONS WITH A CONTRACT CHANTITY OF ONE UNIT. ALL COSTS ASSOCIATED WITH THE DESIGN, INSTALLATION, DEWATERING, MAINTEWANCE, EARTH DIRES, TEMPOPARY PIPES, STEEL SHEETING, POWPING, TREATMENT OF POWPED WATER, AND ALL DIMER MEASURES SELECTED BY THE CONTRACTOR TO COMPLETE THE WORK AND REMOVAL OF THE MATER DIVERSION WILL BE PAID FOR LINDER WATER DIVERSION STRUCTURE ITEM SOS. TOT. THE CONTRACTOR SHALL SUBMIT A MATER DIVERSION PLAN IN ACCORDANCE WITH 565.3.1.2. THE SUBMITTAL SHALL INCLUDE THE PROPOSED METHOD OF DEWATERING AND THE METHON OF DISPOSAL OF WATER PUMPED FROM THE EXCAVATIONS.
- 7. THE MATER DIVERSION SHALL BE DESIGNED TO ACCOMMUDATE THE BOTTOM OF EXCAVATION GRADE INDISATED OF THE PLANS INCLUDING ANY AREAS WHERE THE ROCK EXCAVATION EXTENDS BELOW THE REDUIRED ELEVATION. SEE FOUNDATION NOTES FOR ADDITIONAL INFORMATION.
- 3. THE MATER DIVERSION STRUCTURE SHALL BE DESIGNED. CONSTRUCTED AND WAINTAINED IN A MANNEP THAT WEET'S THE REQUIREMENTS OF SECTION SOT. SOT. THE FOUNDATION NOTES, AND ALL APPLICABLE ENVIRONMENTAL REQUIREMENTS.
- 4. THE WATER SEVEN WITHIN THE HEADWAY AND MINGRALL EXCOVATIONS SHALL BE WASHINGTONED BELOW THE BOTTOM OF FUOTING CRAPE. SO THE FOOTING CONGRETE EAR BE PLACED IN THE DRY. DEWATERING SHALL BE CONTINUOUS UNTIL THE HEADWALLS AND WINGHALLS ARE BACKFILLED TO THE ELEVATION OF THE SURPOUNDING WATER TABLE.

UTILITY NOTES

- THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING AND DETERMINING THE LOCATION AND SIZE OF ALL EXISTING UTILITIES, SHOWN AND NOT SHOWN, PRIOR TO CONSTRUCTION. THE ENGINEER SHALL BE NOTIFIED IN APPTIBLE OF ANY UTILITIES FOUND INTERFERING. WITH THE PROPOSED CONSTRUCTION AND APPROPRIATE REMEDIAL ACTION SHALL BE TAKEN BEFORE PROCEEDING WITH THE WORK.
- 3. THE CONTRACTOR SHALL MOTIFY DIG-SAFE PRIDE TO CONSTRUCTION.
- A. THE EXISTING 6" HOPE SEARS FORCE MAIN TO THE WEST I INLET SIDE! OF MH 110 SHALL BE PROTECTED THROUGHOUT CONSTRUCTION. CONTRACTOR SHALL BE RESPONSIBLE FOR CONSTRUING THE LOCATION OF THE WARM AND SHALL PROTECT AND USE EXTREME TARE WHILE WONJING EGUIPMENT AND MATERIALS OVER IT. A MONIMUM OF 4" OF COVER OVER THE PIPE SHALL BE MAINTAINED AT ALL TIMES.

STREETE THEY

BBOBSNA

DON LOCAT

OF BRIDGE NO

SUMM	ARY OF BRIDGE QUANTITIES - BR. NO.	121712	1
THEN NO.	ITEM DESCRIPTION	ברן ראב(ום	(10.17
209,201	GRANULAR BACKFILL BRIDGE FF	13.0	CK
500.0201	ACCESS FOR BRODGE CONSTRUCTION	1	0
500.0202	ACCESS FOR BRIDGE CONSTRUCTION	1	12
503-101	MATER GIVERSION STRUCTURE	3.	U
505.201	COFFERDANS	1	- 0
505.202	COFFERDAMS	1	U
504.1	COMMON BRIDGE EXCANATION (F)	365	6.8
504.2	ROCK BRIDGE EXCAVATION	17.5	CY
558.	STRUCTURAL FILE	105	0.00
520.18	CONCRETE CLASS & ABOVE FOOTINGS (F)	38	Cf
520.213	CONCRETE CLASS B. FOOTINGS ION SOIL) IFI	6.6	2.4
520-12	GROUTING VOIDS IN BACKFILL MATERIAL	74	CY
534. 3	WATER REPELLENT ASILANE/SILOXANET	5	GAL
538.2	BARRIER MEMBRANE, PEEL AND STOCK - VERTICAL SURFACES IF	7.5	51
541.4	PVG WATERSTOPS, NH TYPE 4 (F)	44	LF
544-	REINFORCING STEEL OF	14567	LH
567.1	SILICONE JOINT SEALANT LE	5.1	LF
1,002,1	PEPAINS OR REPLACEMENTS AS NEEDED - BRIDGE STRUCTURES	- 4	П

* NOT A BID (TEN

FOUNDATION NOTES


- 1. ALL FOOTINGS SHALL BE FOUNDED ON A MINIMUM 12 INCH THICK LAYER OF STRUCTURAL FILL-PLACED OVER THE ACCEPTABLE BEARING WATERIALS DESCRIBED BELOW. THE CONTRACTOR WAY SUBSTITUTE UP TO TO INCIDES OF CLEEK STONE STRUCTURAL FILL FOR THE CRUSHED GRAVEL STRUCTURAL FILL IN ACCORDANCE WITH 558, 2. 1.3 AT NO COST TO THE DEPARTMENT.
- 2. THE EXISTING WISCELLANEOUS FILL. THE NATURAL GLACIAL OUTWASH DEPOSIT, AND BEGROOK INCLUDING ANY MEATHERED AND FRACTUPED REOPUCK ARE ACCEPTABLE FOR SUPPORT OF THE PROPOSED FOOTINGS FOR THE INLET AND DUTLET HEADWALLS AND MINGWALLS. EXCAMATION OF THESE MATERIALS BELOW THE SPECIFIED STRUCTURAL FILL THICKNESS IS NOT REQUIRED. AND TOPSOIL, WOOD, OR OTHER LASTITUBLE MATERIALS ENCOUNTERED BELOW THE PROPOSED BOTTOM OF STRUCTURAL FILL GRADE SHALL BE EXCLUSIVED AND PEPLACED WITH STRUCTURAL FILL. AS DIRECTED:
- 3+ THE EXCAVATION TO PINAL GRADE AND THE CONTROL OF WATER SHALL BE COMPUTED IN ACCOMPANCE WITH SECTIONS 503 AND 504, AND IN A MANNER THAT PREVENTS DISTURBANCE OF THE FOUNDATION SUPPORT WATERIALS. PLAPING EQUIPMENT SHALL BE PROPERLY FILTERED TO PREVENT LOSS OF FINES, ANY DISTURBED AREAS SHALL BE OVER-EXCAVATED AND REPLACED WITH STRUCTURAL FILL AT THE CONTRACTOR'S EXPENSE. STMP AREAS SHALL BE LOCATED OUTSIDE A THEEV SUPPORT LIVIT BELOW THE ABUTMENT AND WINDWALL FOOTINGS.
- FOR LOCATIONS REDUIRING ROCK REMOVAL. THE REQUIRED ELEVATION FOR BOCK REMOVAL SHALL BE 12 INCHES BELOW THE FORTING TO ACCOMMODATE THE 12 INCHES OF STRUCTURAL FILL-ANY ROCK REMOVED BELOW AN ELEVATION DRE FOOT LOWER THAN THE REGULARD ELEVATION WILL BE CONSIDERED AS EXCESS REMOVAL AND WILL NOT BE PAID. NO PAYMENT WILL BE WADE FOR STRUCTURAL FILL THAT IS REQUIRED TO REPLACE EXCESS ROCK REMOVAL.
- 5. FRACTURES OF SEAMS IN THE BERRUCK SURFACE EXPOSED AT THE BOTTOM OF THE FOLKBATION EXECUTATION SHALL BE CLEARED AND GROWTED IN ACCORDANCE WITH SOS. 3.2. DR CHINKED WITH CLEAN STONE FOR STRUCTURAL FILL 49 DIRECTED
- 6. PROTRUDING COBBLES AND BOILDERS ENCOUNTERED AT THE FINAL EXCAVATION LEVEL SHOULD BE EITHER REMOVED AND REPLACED WITH STRUCTURAL FILL OF SPLIT TO PROVIDE A LEVEL SURFACE.


PIPE LINING NOTES


- IN THE WORK SHALL CONSIST OF THE REPAIR OF THE CULVERT BY THE INSTALLATION OF A CEMENTITIOUS LINING CENTRIFUGALLY CAST IN PLACE FOR THE MATERPROOFING. SEALING. STRUCTURAL REINFORCEMENT AND CORROSION FROTECTION OF EXISTING CORRUGATED STEEL COUNTRY PIPE. THE CENTRIEDSHIP CAST CONSERVE (INCP SHAP) ENTERN OVER THE SPECIFIED LENGTH FORWING & CONTINUOUS CONCRETE PIPE WITHIN A PIPE-
- 2. FOR JIEW BOZ. 41190 CENTRIFUSALLY CAST COMPRETE LIVER FOR 90° CMP. THE APPLICATION THICKNESS SHALL BE A MINIMUM OF 2". UNLESS THE STRUCTURAL CALCULATIONS SHOW A NEED FOR EVEN GREATER THICKNESS. SEE SPECIAL PROVISIONS FOR DETAILED REQUIREMENTS.
- 3. USE TIEM 520.32 IN GROUT ANY VOIDS FOUND IN THE BACKFILL MATERIAL SURROUNDING THE EXISTING COLVERT FRIDE TO INSTALLING THE CONCRETE LINER SEE SPECIAL PROVISIONS FOR DETAILED REQUIREMENTS.

STATE OF NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN DRUDGB 800 181/130 DWN SEDIORS STATE PROJECT 18756 LOCATION IN URDOTE UN OVER BUWMAN BROOK

			BRIDGE NO	TES					COMPANY SHIRM
		REVENOVS APTER PROPORAL		BY	DATE		200	DATE	2 0 17
100	antec		DESIGNED	Detaile	06/2917	CABANAD	TAZ	06/2017	नाम पामाका
	attice		DRAWN	TIW	09/2917	CHOCKED	TAT	66:2017	
			QUANTITIES	TAY	09/0917	CMECKED.	13624	9672017	128-3-2
OB	SHEET SCALE		1881/B DATE		RECEIPT.	MODULI NO	24.2	T1 H0	101A: XIZE13
TES	AS NOTED		BEV DATE		X-At	101 (160)		8	23







BORING NO. BO1

			AMPSII	RE DEF		NT OF	RMS	PORTABO	N A4. 41.		BORING NO), B	01
						EOTEC	HNICAL	BECTION		N/A	STA	OK.	
ADJE DESCE	ANTO:	ME RE	MED So	elapen	era NH	114	_	BRID	DOLENO	NIA		NH Ronte	
<i></i>	u 121	-	DIMATE.			EOUR	SERVEY .	SWAFT, ER	TASING	COPE	FLEVATION (N) STARTIEND		.u. 29
LATE.	105	20000		901TQ4	читы	7407		9	Ph/	7-		Рюте јан	CO.
			P	h -Ne-di-	: - M F	02F 0	1.2	110	. :	112	NSPEC FOR	Barry An	
	- 62 a1		210.3	" -	-11	- 1	11 .	J.	Charles 45-C		CASSIFIER CASTINOPTH (b)	6,4 1027301	
	· Intellig		F1 44		.ku-	90.00		ALLEC	•			10001.000	
14.500	201111	Llı 4	11 /4	ABDAT P	·15			FEL	O OLAGOP	CATIO4	AND DEMARKS		21000
û -	-01	-29.9	7	5 :SAVI	4 70)	7.1			JPSJJIL fra Lipoteershih Petitor kanti		Jery Issaeris SAND new 648 p.	and Inka	-
	ا د	328.4											
	33	2204	4	_		LII	YVar-	culur lummed I	lease (see each	i farine-	C C Se mand a rio		
5 -			3	8. 44.	9 9	h2	13 DIPER	munit make	ricas raesti ricas raesti	IX-BITT	SAND Troch (neight aithn byenn cause firm airithea	red Hara Min	-
									-CH AC	и ал	W.54		
	54	221.5							UM-Schendari	EARDE	CK BURFACE		
							T-brown						
W -					-	17-7	mar 8	- Lailie Salland-firm	an tables for co	distance with	remograndians b	A ZIEA	
													100
				E-	R Fu		Internal	marchi (43)	ANTE by:	mg= tro	fy Anabarod, gray with yes par 15 mig neg paradien star ng	4 Other	di-
= -						l. p 143							1
				0	1 7.0]		CONTRACTOR IN	DISMING HR	ANTE FINA Number	Lies and	ė, riadiolist galay seli na ip radiologijosių digir	h bruwi: mig Spred	
æ						- 11.1		Dr.	0 -500	ener Gord	1001		-
25 -			1										
- NO. CO.	seraka Santa	Eldi	In	burn	Tal) HETTING	140 S		NOT COM	ERVE HIJLE Park h	100	a Saurias an	Cause Lagran	r mari
설	ung- Wa	PERHIP D	* 3 m	r.		obly Sufficient		11 4	UNI HAN		and Care Appendix	20 to	· ·
ii		Legister		E	2 1	Market No.	0	. 60	Males No	-	(In	1105 2	
	CALLES .	ker.		18	36	very Suff		5	Feet and Servicement	1	-	.4 1	-
1:	·L r	eret eraku		60	N ·	April April 4811	1 /	erje vegt. erit Werde	li,e		ENGL	JESU HUEBE	

	TE DE	vennu		BOR			RANSPORTATIO	No. 2		BORING NO),	B02
M	ATERIA	LS & AI	ESEAR	CH BUR	SAL G		NICAL SECTION			SHEET NO.)F F	OF Z
				RD 1615		та	BRI	DOE NO	N/A	BASELINE	Nº No	ote4
)ESC	RIPTION	GROIN		inplacem		ECT-NA	ent Swelet	CASSNO	CORE	FLEVATION 'N	2 4'	250 7 40
L	1941	GH(I)FI		_	9.10 A.	F. Crash	GINI SPONENCE A	(LACKS)	brew			NHEOT
296.0	Augal	1	also.	A 000	SE HAR F	0.000	. 715 VF = 14	Del	Più LRG	MSPEC TOR		Arsenesi. BAA
		-		_		- II-I .	a n nti Aspan.			CLASSIFIER EAST-MORTH (5)		382 JT000
T STIN	die u Helele	Tan.	1 . W		اري السابي (السابي) (الاستان)	1		D DL/G65	-GATION	YHD-JEMVDK6		5,779.0 5,779.0
0	0.4	40.				-	Dies ASPHAL' I	WARMEN.				
			50 Ji 19	E Sayı	0189	!	ValV dame id ek y sperimed med in	utov FNES Isana Iran	SANS III ASA Sar	coarses Final graheat 11	أأدثت بشأ	·
									.1			
=	1		1 1			ы.						1
			-	7 5µ1	0.548		**** ****	PILE SASS				
III .			0 4									
			T	, ABA	# D [Bir]	nin)	Medium dense: elk	is yellow. Pili	E 3/7401. br	açe madium minit. bi	Me age	
						- 19-11						
iđ ·	45	3358				-	Witten som charge	larer along	al are la conse	s at 5		-
			14	54 64,	161-	1-1	Medium penser (g.k.) aprel framiliera no mondad de wat (da)	al seems	e grave i tro ditro leyen	te chame vand mice count grey St. Look	notur skrimti	1
								CF.	CIÁL OKITY	WASH-		
21			" ,			75. d	Medunishna ce	name the	SWD THE	a line preval fractice		ed be
			1	15W	1889		Make the fresh sand	MARKET &	To ayura u	فيحان أأالة وكريمه	ASIAN SIN	F .
26						-						
			1	Bri	Diffe			n_=INE 5#	O His sit	mace medium sand	Impren	1
				(SE SM)		!	ratesand					
	desire.	n.m. Ind Sa	PIF	10.000	-10HEUR June	S 1005		-Class HC41 (tasy)		or Describera	State	
E T	Company Total Sci	ARRIT!		.7	4	Ge4 19	0 4	4-11-1		Desir Care Adverse	E%	30%
a	Jan Jahran Terret	Fig.			-3	Notice Std Rad		dense k	PDF-	File FN-J-	11/2	100
5	Augus -	-11		d	91	wm Mi H/s	With Mary	Viery Distra				
98	No Pac			60		sery dem	WOR WAS	a lumen		ENGL	,2,71	

BORING NO. BO2

BORING NO. BO2

MA	ATER:	ALSA RI AME <u>Bi</u>	DFOR	он вия В 1 <u>61</u> 5	SAU GE		THANSPORTATION MAY SHEET NO DF STATE NO NICAL SECTION NICA
		u soca II - o	n_56.	10 (A)	All All	SHOW!	FIFTA CLASSFICATION AND REWRINE
70 -		-100	c	5	0 164	IE II	CR, ACCAR, TRUTAVAS L Life PS 2296, base reduce and trace of verviously weathers: mik highest something before 2296 and with highest something before 2296 and with the common of
				с	4 × JIIIOJ		uses legal material systems of secure by tractured payment from a contract granter. See E. Bronn of the act of them are sent majerity result and mode does to extend to several disks this granter. If the E. Bronn are sent an extending the secure of the se
JE -						15-14	
40 -							
46 -							
G -							
55 ·							
66 -							
Œ -							

BOR NO NOTES

- TOR BOR NGS BOT THROUGH BOG THE WHOOT PERFORMED SUBSURFACE MYEST GAT THS AT THE 5 TE IN FEBRUARY 2011 ADD TIONAL BOR NO LOUS AND GEOTELMH CAL INFORMATION S AVAILABLE ON LINE ON THE INVITATION TO 8 DIMEBPAGE AT WAY-ON BOY/DOT IN THE SPECIFIC PROJECT S PROPOSAL PACKAGE ADD TIONAL BOR MGS FROM THE 1964 STATE PROJECT PASSE ARE SHOWN ON BRIDGE SHEET 9.
- 2 MORTH MG AND EAST MG COORD NATES REFERENCE THE NORTH AMERICAN DATUM 983.
 1886 AND ELEVATIONS REFERENCE THE NATIONAL GEODET A VERTICAL DATUM OF 1929
- SUBSURFACE COMO Y DNS ARE ANDRY ONLY AT THE EXPLORATION LOCAY ONS AND COULD MARY AT OTHER LOCATIONS ON THE SITE
- 4 GROUNDWATER LEVELS SHOWN ON THE LOGS REPRESENT THE COMO T ONS AT THE TIMES OF MEMSUREMENT AND COULD CHANGE TO RESPONSE TO SEVERAL FACTORS. MILIODING PRECIPITATION AND TERRAIN ALTERATION.

	S' DEPARTMENT OF	TATE OF NE				DES/	TOKS.	
119		TRANSPORTATI	DROLLIE AL			A F Pho		6110
0.0	CATION IN ROUTE 14 OVER BE	IWMAN BROOK						
	BORT	NG LOGS (S	HELT	1 OF	4)			emiliani: questr
	TEVESONS APTER PROPOSICE		BY	DATE		EK.	DATE	6 9 17
		DI-\$1GNED	DEM	08/29 7	alataly 12	TAT	W201	नाज साम्राज्ञात
-		18 4 9 5	TIW	05 6 7	0.00	Tá	-0:2017	40.0.5
		01 April 199	TA:	08.56	Percent Rends	12,24	as thirt	28 32

X A001 (160)

12

ISSUED ATE

BDR NG PLAN \$1900000 TORY ATOM OF ATOM SHEET SCALE


NA (2_Borngleg 0) AS NOTED

BORING NO. BO3

M	ATERIA	NEW H	AMPSI FREAR	HIFS DEI	PARTAE EAu G	PORT BUT OF TRANS EDITECHNICAL	SECTION	GE NO	N!A	BORING NO SHEET NO SIA BASELINE	OI-K NH Run	
0ESCI	RIPTIO	y Di	lvad R	оржет	iom NH	1.4				FLENATION IN		407
		GROUM	CWATE	×		EQUIPMENT	MMETER	CASING	COME	START/END	2977	
DATE	Th/E	DEFILI	ELEV ALL	BATTON	Acute	F57.10 0	1.25	4/11	175	NSPSCTOR		BEFERV.
J.	111		J	4.	.31	proper all to		DRIL	RIG	AURSSHILE		0,9
						900, 115 . 900, 116	Participation.	OME 45-0	. Iregi ng	5A50/6097 (0)	N _e T)	00:170659
e gr	Harris III	 107 - 107	0.5	TOPE STATE	1 aur (0 800)	11-	FIDLO	0_4660	VGATION	чно починике		q vy , 1, Eat b
			a a	ISION	H	Lucisti II "	. gH yellows	Hürdəri dil	y PINE SA	MO had dot flore. I	шват чь	
	70	-0				Manh	rator arange	i karr jedav	rwm dwy	loom hour #71		-
			e.	34	U::010			and the said	may St. L	на падинале Та	peni	
				2 .2		LILS LT/MEN	10					
								-FLA	CIA: ILIT	W/5/4		
			rsic	5.1	0 5 [25]	ET Z. IND	yakan amara	y we make the way	HANGE P.	secution! s		
ın ·						Advan	oc on, w	n galler (N)	rough rola	T E of A C mort &		1
						Tork .			IF	edim sani hyus sa		۳
17	+5	/26	,P	н	Jici	Is a Dark	A	PER	n Eliane	res ROSA FRASAE	VCS	-
						111.5						
DI				г	48 1191	In c	TOTE LUAN A CONTROL A CONT	III 1)1 . 21 t	d medierali Plant E i Samene si Sca	ns fractional group from on the drop of the frac- group on harmons suit	we line	n
						Jun	Bon	nm nt Expo	י (6 מאים	U 41E 5,581		
25	-											
MINISTER STREET	tamila:			B.pm.	*OHESIA		grib str Boxation	(560 5) (3 (800 5)		as Dearmonna an Armit of Marie	-Chairm West	2 21774
s.	Thin Au-	anni O D 6 - Ida 301 Paka	3111	2 2	4	Series Series	11	AHP 46 LEDM Medium Di		TAME TOTAL TRANSPORTED TOTAL T	225	AP-
2	Object Co. August	r Fig.		- 18	31	Carl Saff	1 K	Territory David		IEr	7	0%
	101 241					Har	Win Magr	. 4		ENOLI	SHI.	

BORING NO. BO4

SCHEMENT County	M	ATERIA	MEW HAMP	ARCH E	BURBA				SECTION			SMEET NO OF	
Column						I NO-I	4		ERIC	CE NO.	NIA		
Table						1		MENT	SAMELER	CASING	DORRE		
Section Sect	u w	THE	_		TOV III	TOV.	Pirt		3	IW	nic	ORILIER _ N. Perce (NH	
Section Control Cont			F	177				21					
### 1 # ### ### ### ### ### ### ### ###	3	: .**F			:	7	dar."	٠	:				
### ### ### ### ### ### ### ### ### ##	r=n.						To to	.1%					Viene.
STREE BELANCED STREET	0		429.4				mr :	Cont. In Marke	THE LAND	PROBLEM Wali Riso	guerdines. FINE BAN	ulera transi loku. Disume sua sekile gilonal killa	+
### Well form 1					·- 21		-17	E40, 112	ku tersisa	12 119E4 mot			
### Address and learning and that the frame of the first probability and the first probability a											.rl		
Section Sect			27H 9							CIGNOVESS	roman	CK SISTATE	<u>. </u>
### ###							17	Adams	and having only				
### Comparison of the Comparis	5							91	Pat.				
						1 -91		The beautiful to	comment att	201 B III	Office last	DM: 101: From Witch's	ΨΨ
									-		- 44		
25 26 27 28 29 20 20 20 20 20 20 20 20 20	_									HI-THE LOCAL	and M n	1111-2 2 4.	
ACTION SERVACE THE STATE OF THE													
ACTION SERVACE THE STATE OF THE	٠.												
ACT OF SECTION STANDS SECTION													
ACT THE SECTION STATES AND THE SECTION OF THE SECTI	o.												
	o.												
2 4 4 4 4 4 4 4													
T Per Well from 6 Set 5 II Looke Same CPA (2%) II II despet Popul The Set 5 II Set 5 II General Trace 10 III II I													
2 Oper-Fin Ann	P.	400 0	1 15000						aQr. 164	FRAE NOVE	100	profession of training the company	Darley,
	25 9 9 9	April 10 Rept in The Wes	l deprez unario∏ = i nitum	ń	r.		un salme un Sali Sari		40% 144 (8-19%-144) 3 4	ERGE FULLE CAPALL OFF TRANS	5	producer of transport Major Services (275 - 227) or a Constant C	, , , , ,
E ABOUT THE ACT OF THE ENGLISH	25 25 21 21 21 21 21	Alex III arcjet ac than Wes III Plan	d dispress uses di Di Pierra nd fusion dignal Problet	n I	r. G		un salma un Salt Sart Uniter St		30% Ted (8.00% http://de. 25 41 41 42 42 42 42 42 42 42 42 42 42 42 42 42	ERVERIALE Vermone Local Water Ne	5	production and legand Magin Laws materials Adoption 277 (277) form CDS (277) dips (277)	6 6 5 5 5 5 5 6



BBV DATE

13

X A00" (60)





BORING NO. BOS


744	ख्याम्। ध्य	WATE	PR.							ELEVATION No.		/27
. dr. sal-	- (- l) - (-)	100 100 1441	Parties De l'estre	MATERIAL STREET	FRUE 500 1000 1000	UF NT	124 124	IPQ	ECHAG NAME NAME NAME NAME NAME NAME NAME NAME	STARTVEND DRILLER VIP NSPEC OR NUASSOCIA	Heroo 16 Harry A G	inaren ioa
*11-07 to	4	0,4	nyer Shill	ил: ,п	1.15	211	FIELD				10010	1708
04	236 7		26	[24]	FE .	Oark his Violani Dualisis	on any sec	TOPSAIL II ORK SOMI	TvEbium vog mok ha	o Improedu Invent PNE SAND Nace for groups	18 18.00	:
23	∠á4 H					Atherse lign 1	of unlikely	ersones er alle bro	a ji Je Bhalka Pougil va v	or safebook several, wed receal bi	adetice	¥
			L	→ E [36]		Voly la copye Classific Yest	nwaninj	TREASON OF THE	a, moderate no es vicilio no bracción	hy Surus Merkeli, i Austria Sur i magazinek, jihos Autorea	na jiés Ig	1
					-		a	altum of Espi	ewinn (6)	TOTEL STORY		
parmit s	42			*OHESIA	F Right programs as Soli		ų:h ч ms3,1;	-[-574][\$() 0.5 -(-574)[\$() 0.5		on Demonstrates	-2naun West	IZ
	O 4	04 236 T	04 2267	04 226 T 3	04 226 × 3 12-1			100 100	100 100	Section Sect	CALL Style Cal	Section Control Cont


BORING NO. BOG


MATERIA	ME BEDFORD	RE DEPARTMENT OF THIBURSAL GEOREC \$ 16158 placement NH 4		BORNG NO. BU SHEET NO OF SIA CV BASE, ME NH Roote FLEVATION (6): 245	4
477 184 1841 1841 -	GECURANATE CONTRACTOR	#30,485 ************************************	SAMPER CASING CORE	STAFFIEND WITH ORLIGH I POSSIBLE NIGHT FOR BARE WAS LASSIFER DAS	TIL POD PODEN.
T=n. / 1.1.4	11 (1 ma)	Service Service 10	LETD CTVERKWINDM		A table
	4	6 470 SW	Mythic serve of the extraor. TNI 541 ed, here cover and here maken and	IP - dhe conselline graval infra nazarazal mali libera Triana In	
4 5	25		Wash order clary a from the brown to she	1	•
	,		-GLACAU XUIV	VA-94-	
5	1	B. der	come of will FME SAND obtains occasion race on nounconfusion layers also SIL.	and Par Open Geor FRE SAND	
			Scienced horsy with railer to brings rate	fe-from II m -4"	¥
	18 18 18 18 18 18 18 18 18 18 18 18 18 1	9 total	дина медициятие воеф вые зависи матично помартия в дво об		
0 7		7.7	Approximate Section Special limits with the bit Citary's very logs Section 6	DK SUIV ACE salvereir weed teering and tech	
		311/6/1	Capitant malawish wad rest medical ryper of their gards I-444 in Fis. rgang RLL 24 45 SIN	ly material to source (pay page of Mon. III (Mon. May	
		75,7	Butter of Equipment (b)	- 6 h (E) - 47 a)	,
2/					
¥					
ACIDE DETAIN	TARE 4. 4 depres Amount DE 100	CHESAR BAC burston a sale	A a territorial	or Description Processing projects of layers Mayor Services and Control	la
Si eth a	nt tuan dan Payler	4 Sat 4 Union 5 5 (4 Sat)	Sell 1 Al Makes Norm	ome CUP (81 On OF 255 Only 15 (5)	




















OLTLET FOOT NO MASONRY 6 E =



OUTLET FOOTING REINFORCEMENT





TYPICAL FOOT NG SECT ON




TYP CAL FOOTING REINFORCEMENT NLE -

		STATI		N * B (REA)	OF BRIDGE		
		OUTLET	RRICOR	G DET AI	LS		6176 FERROLL STORM
Stantec	REVENUS AFT		DHAWN OF ANY TIES	1GS 08.45	a disk a	BY BATE DBW 18.201 TA 8.2017 TA 88.2017	28. 32
MINIOWERS THE DIGHT MIGHT STALLS AS MODED			ISSUE DATE		1007 (1.90)	24 18 161 T	10142 8.25513 23







SOUTHEAST WINGWALL

REINFORCEMENT

5(4[E t - 1 - 0 "


75 - 45NE1 @ 1'-0' (F5)

15 - 45NE2 @ 1'-0' (N5)

2 - 45NE4 (1 N5, 1 F5)

2 -

NORTHEAST WINGWALL
REINFORCEMENT





TYPICAL REINFORCEMENT SECTION


	OF NEW HAM			
DEPARTMENT OF TRANS	,			
IDAN BIDLORD	DRUINGE (NO)	151/15X	STATE PROJECT	16776
LOCATION NU ROCTE LIA OVER BUWMAN BE	Secur			
OUTTIET W	TANCESS ALL DES	PAHC		ESHIR
COILEIM	INGWALL DE	LAILS		



	OUTLE	T WINGWA	LL D	ETA.	ILS			parelle desert
	SEVENING AFTER PACPOSAS		BY	DATE:		ETY	DATE	15 or 17
		DESIGNED	165	08/2917	(BRXXIID	D574	\$82017	FILE WITH MER.
		DRAWN	730	08/0917	CHOCKED	TAT	08/2017	10000
\vdash		QUANTITIES	JGS	08/09/17	CHECKED)	TAT	467017	128-3-2
+		ISSUE DATE		REDGIOG!	инопод во	2912	TI NO	10TAL SUZE13
+		BEV DATE	\neg	30-A0	101 (160)		21	23







TYPICAL SECTION W/ SIMULATED STREAMBED MATERIAL

STATE OF NEW HAMPSHIRE

DEPARTMENT OF TRANSPORTATION * BUREAU OF BRIDGE DESIGN
TOWN BUDGERO STATE PROJECT 18136
LOCATION NURSCITE 114 OVER BOWMAN BROOK



	CULVERTIN	ILET AND	HUTL	ELL	DETAIL	S		16 - 12
	SEVENING APTER PROPOSAL		BY	DATE:		ETY	DATE	16 0 17
		DESIGNUD	DSW	06(29)7	(SBXKID)	TAR	06/2017	जाम पामित्र
\vdash		DRAWN	TIM	06/2017	CHECKED	TAT	66/2017	100 2 0
\vdash		QUANTITIES	TAT	06/2017	CHECKED	pear	96/2017	128-3-2
╁		ISSUE DATE		REGION	MODEL NO	26/2	TEL MO	10142 X-25E13
+		REV DATE		X-AI	101 (160)		22	23

Slat.	Sire	Lengts	ARIGIN	Fyrm	A	Б	C	D .	-	F	0	Н	1	K	Ŕ	
WE1	45	9'-0"	53	STR												
WES	49	9' -0'	53	STR												
WF3	115	6'-3"	8	STR												
WHA	四日	41.3"	- Fi	SIR												
WES	#5	24" -0"	. 20	STR												
WF6	#5	16'-4"	20	STR												
WF7	略	16-9	.20	STR												
WES	p7	6' 2"	17	NB		5.0	1' 2"									
WED	67	6'-2"	37	MB		5'-0"	1'-2"									
V/9F 10	05	5'-1"	48	NB		4"-3"	0'-10"									
		MARY	10îAL												_	
πEM#	DESCR	NORTH		#3	p 4	\$5	. #G .	#7	#48	#5	#10	#11	#14	#15	100	LA
544	RENFO	RONG 8	EEL !			1962		682		175					44	F4
544.11	MECH.	CONNEC	TOR I													
544.2	EPOXY	COATE	3													
544 21	EPOXY	WECH (OBNN I	i		1										

Mi	NA.	528	Langth: A	- ecre	Type	A		C	D	E	2	0.	Н	1	8.	R	Ü
465	///1	#6	8,-0,	15	STR												
100	W2	*5	9'-8"	51	SIR												
500	NЭ	#5	10'-10"	13.	STR												
UNA	Md	銀布	9-11"	43	STR												
500	N5	W5	57 -0"	7	T1	08,	0'-10'	1'-2"	0'-10"	1'-2"		0, -8,					
500	W6	#5	21.4"	-4	10	4'-5"	13'-4'	4' -0"								4'-3"	
lete	r ta	See le la	MMARY 1	ortas 1	uli Escèll	+ FBb = 1:											
_			IPTION.	U1 ML	<i>\$</i> 3	194	#5	#B	\$7	部	#8	. #10	#11	#14	#18	to	TAL
544			IRCING ST	TEEL	***		516	220	-	- ML	714	1			WIM		38
644.	.11	MECH	CONNECT	FOR													
544	2	EPOXY	COATED														
\$44	27 1	EPDXY	MECH. CO	ONN													

Mars	Sign	Lange	# PARCIN	Type	A	В	C.	0	E	Ŀ	G	H	T	16	8.	0
EW1	66	10"-0"	15	STR												
EW2	#5	10.5	11	STR												
EW3	65	11'-0"	14	STR												
FWA	615	B-11*	14	STB												
EW5	A5	5' -0'	. 7	71	D' -6°	0 -10"	1'-2"	0'-10"	17-21		06"					
EW6	#5	21' 4"	-4	10	4'-0"	13'-4"	4'-0"								4'-3"	
	OR SUI	MMARY	"OTAL	WEIGH #3	T (lbs):	#8	#F	27	éB.	#B	#10	#11	\$14	#18	TO	TAI
544		DROINGS	10275	14.3	Med	555	243	4-1	HCI .	40	-W-1LI	4-11	¥14	PF 1 D		98
544 11	-	CONNEC				201	조석단								- 41	34
	1	CONTEL			1			_							_	
54427		MECH C									_				-	

	Mark	Sue	Lamph	A Prepare	Type	A	В	C	D	E	F	0	Н	3	K	Rt J	3
Г	EF1	#5	9'-0"	44	STR												
	EF2	119	9' -0"	85	STR												
Ī	EF3	#5	8'-3"	6	STR												
ľ	EF4	119	6'-3"	12	STR												
Ī	EF5	#B	24" 0"	30	BTR												
	EFG	95	16 4°	20	STR												
	EF7	ρ5	15 -5"	20	STR												
ľ	EF8	87	B'-2"	17	MB		5-0	1'-2"									
Ī	EF9	87	8'-5"	29	NB		7"-3"	1'-2"									
	EF10	115	7'-1"	40	NB		63,	0"-10"									
-		_		107AL													
1	TEMB	DESCR	PTION		构	#4	#5	#10	#7	*8	#5	#10	#11	#14	#16	FOT	FA3
f	144	REINFO	HONG!	S EEL			1939		734		187					551	U9
ċ	94.11	MECH.	CONNEC	TOR													
à	942	EPOXY	COATE)													
I	644.21	EPOXY	MECH 0	DONN !													

Mark	Sau	Langle	# Name	Type	- 6	B]	C.	D	E	+	0	H	- 4	100	H	0
NW1	ME	6, 6,	22	STR												
NW2	#5	6, 4.	22	STR												
NW3.	#5	19"-7"	24	STR												
NWA	#5	19"-7"	2	STR.												
SECT	NON BLI	MARY	TOTAL	WEIGHT	[libs]:										-	_
пЕм≉	DESCR	IPTION		#3.	#14	#5	#8	#7	模	#9	#10	#11	214	#18	TO	TAL
544	HERREL	RENGS	TEEL			750	123								TU	73
D44.11	MECH.	COMMED	TOR.													
544.2	EPOXY	COATED)													
544.21	EPDXY	MECH 0	CONN													

Mars	Sten	Tamps	# Places	Type	A	B	C	D	E	F	G	Н	2	K	R	0
NE1	#6	B' -8'	15	STR												
NE2	飾	B' -8'	15	STR												
NE3	鹤	14"-7"	22	STR												
NE4	約	14' -7"	5	STR												
SECTI	ON SUI	MARY	TOTAL I	WEIGH.	T (lbe):											
TEMP	DESIGR	NOTION		#3	#4	45	#6	#7	EN	#9	#10	#11	014	MIB	ारा	ML.
30.6	HEMPT	HONG S	STEEL !			499	1972								89	11
506.51	MECH	CONNEC	TOR													
344.2	EPOXY	COATE	3													
344.25	:EPOXY	MECH O	DINN.													

Mars	Size	Length	in Pleases	Type	A	p.	C	D		F	F3	D	J.	K	Л	- 5
SW1	WB.	9'-8"	15	STR												
SW2	#5	9'-6"	15	STR												
\$1003	#5	14"-7"	20	STR												
SW4	#5	14"-7"	2	STR.												
			TOTAL													
TEMM	DESCR			43	P4	35	#B	97	. 198	#3	#10	#11	814	MIR !		TAL
iga .	ASME:	RONGS	STEEL			464	220								-71	04
44.11		CONNEC														
94.2	EPOXY	COATE)											1		
44.21	EPDXY	MECH 9	CONN													

Max	\$120	Length	# Please	Type	A.	[ii	E.	D.	. 6	F	6	11	- 1	15	A	0
SE1	#6	8, -8,	14	STR												
SE2	#5	8, -8,	14	5TR												
SE3	#5	111-27	26	STR												
SE4	A5	111'-10"		STR												
			TOTAL													
LEMM :	DESCR	PTION		K3 .	#4	95	ME	97	m	66	#10	#11	814	MIR.	TO	TAL
544	RENEC	RONGS	MEEL			483	170								64	2
544 (1	MECH	CONNEC	TOR													
586.2	EPOXY	COATED	3													
541.21	EPOXV	WECH D	ONN													

GRAM	D SUMMARY TOTAL W	EMPHIT	(thus h										
TEMP	DESCRIPTION	#3	pa	85	448	67	#8	ħÜ.	610	1011	814	WIB	TOTAL
504	RENFORCING STEEL			7188	1377	1396		+606					14557
44.11	MECH CONNECTOR												
44.2	EPOXY COATED												
4421	EPOXY MEGH CONN												

							374	ND4RD	PIDUST	Y BENDS, STARGARD M.H. & SPECIAL BENDS
	pull Col	and age	END HO	CASE I	6	ndrieus (S)	A TO HE	OR DUNCH	Security 1	
2aD		идице	15	MA HEAD IS	844	0(0)	900-0045	LIS	HOUSE	
SUE.	11(0)		- 2	* + 5	925	(4)	A = 0.	4 00 0	Himpi	
43	2 1/4"	5"	5	Ψ*	48	1/5	10		2 1/2"	
м	5	6"	40	•	34	3-	4 1/8	4 1/30	2	
e l	3 3/4	7	5	15	36	1/7	a a	5 1/2"	3 3/4	
100	4 1/2	6,	m'	f.+0°	Jin .	4.1/3"	1:-0"	T 3/4"	4.5/3"	
17	3 1/4	10"	7	1'-2	JT.	0.1/4"	1-2	10"	5 1/4"	
<i>a</i>	4"	H*	er.	11.00	30	10	11-41	40 1/4	0,4	
pù	1 1/2	V-5	11.3/97	1.2	1000	D=F-	richard or			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
		F-5"	15-7-129	1'-10"	honk	Sen /	PSS CHI	I Motho	4 pb-34:4	

ACTIONS IN CORLESSION TO THE BENCH AS THE PROTECTION OF THE PROTEC

	ASIN ST	AMDARD SNG BARS]					0	51	tan	te	С
346	W[KSH]	MAY CHARGE	on (max)	1					~				_
SIPE DESIG- NATION	POUNDS PER FOOT	DIAMETER MICHES	EChina.										
MAII CA	1001	- Mores	II MOHI			STAT	E OF NEW	/ HAI	MPSI	TRE			
43	0.376	0.375	0.75		rank a same							221	
M	6,668	0.500	0.20		DEPARTS	MENT OF TRA	NSPORTATION	A . BUI	MEAUIC	JF HKIDG	E DENK	iN.	
62	1,043	0.625	0.31	1048 B	BEDFORD		BRIDGEN	0.	5516	151 S	ATEPRO	lici i	6126
66	1.502	0.750	0.44	LOCATION	NUMBER	14 OVER BUWMAN	BROOK						
47	3.044	0.875	2 60			REINEC	RCING S	CHE	DULL	7			Mallimb Bileb L
100	3.670	1,000	0.12	1.0	SYNDOWS AFTER JE		THE PARTY OF	DY	DATE	-	EY	DATE	17 w 17
61	3,400	1,128	1.00	\vdash			DESIGNED	JGS		CHECKED	DEM	68/2017	FILE NI-MINER
100	4,303	1,270	1,27	\vdash			THAWN	779	08/2017	CARCKED	TAT	(X:20)7	140 4 4
Fig.	5.37.3	7,410	1.56	\vdash			QUANTITIES	JGS	08/2017	CHECK FEE	TAT	(8/20) T	128-3-3
J54	7,650	7.893	2.25	\vdash			25% r. DATE		NEGOC!	Manther 26)	200	El Bu	TOTAL SEEDS
ILB.	£3.60	2.257	4.00	\vdash			REV DATE	\neg	X-A0	01 (160)		23	23